



Typ: ESTK

Einphasen-Spartransformatoren

Einphasen-Spartransformator nach DIN/VDE 0550

keine galvanische Trennung vom Netz

geringer Spannungsabfall, hoher Wirkungsgrad

Schutzart: IP00 (geeignet zum Einbau bis IP23)

berührungssichere Schraubklemmen

Schutzleiteranschluss am Eisenkern

PRI-Spannung: siehe Tabelle

SEC-Spannung: 230 V

Frequenz: 50/60 Hz

Isolationsklasse: T40/B

Korrosionsschutz durch Harz imprägnierung

Andere Spannungen auf Anfrage lieferbar.

Type: ESTK

Single-phase autotransformers

single-phase autotransformers according to DIN/VDE 0550

without contact separation from the supply system

low voltage drop, high efficiency

type of protection: IP00 (suitable for installation up to IP23)

the screw terminals are protected against accidental contact

safety earth connection at the iron core

PRI-voltage: lock at the table

SEC-voltage: 230 V

frequency: 50/60 Hz

insulation class: T40/B

impregnated against rust by resin

the transformer rare also available with other voltages

corresponding to your wishes

Leistung power VA	Best.(BV)Nr./order No.								Maße/dimensions (mm)							Gewicht weight Kg.
	PRI	100V	110V	115V	120V	127V	Leistung VA	200V	A	B	C	D	E	F \varnothing	G	
	SEC	230V						230V								
630	54306	54326	54346	54366	54386	1600	54406	120	92	118	100	78	6	6	4,1	
800	54307	54327	54347	54367	54387	2000	54407	120	104	118	100	90	6	6	5,0	
1000	54308	54328	54348	54368	54388	2500	54408	135	118	130	112,5	98	7	3	7,3	
1300	54309	54329	54349	54369	54389	3200	54409	135	128	130	112,5	108	7	3	8,3	
1600	54310	54330	54350	54370	54390	-	-	174	118	160	145	95	7	-	10,6	
2000	54311	54331	54651	54371	54391	-	-	174	138	160	145	115	7	-	14,0	
2500	54312	54332	54652	54372	54392	-	-	174	148	160	145	125	7	-	16,0	
3200	54313	54333	54653	54373	54393	-	-	174	168	160	145	145	7	-	19,5	