



Typ: ESTS

Einphasen-Spartransformatoren

Einphasen-Spartransformator nach DIN/VDE 0550
 keine galvanische Trennung vom Netz
 geringer Spannungsabfall, hoher Wirkungsgrad
 Schutzart: IP00 (geeignet zum Einbau bis IP23)
 kompakte Bauform, geringe Bauhöhe
 preiswerte Ausführung durch fertigungsgünstigen Aufbau
 Steckanschluss 6,3 x 0,8
 Schutzleiteranschluss an Eisenkern
 PRI-Spannung: siehe Tabelle
 SEC-Spannung: 230 V
 Frequenz: 50/60 Hz
 Isolationsklasse: T40/B
 Korrosionsschutz durch Harz imprägnierung
 Andere Spannungen auf Anfrage lieferbar.

Type: ESTS

Single-phase autotransformers

single-phase autotransformer according to DIN/VDE 0550
 without contact separation from the supply systems
 low voltage drop, high efficiency
 type of protection IP00(suitable for installation up to IP23)
 compact version, low overall height
 low-priced version due to an advantageous construction
 faston connection 6,3 x 0,8
 safety earth connection at the iron core
 PRI-voltage: see table
 SEC-voltage: 230 V
 frequency: 50/60Hz
 insulation class: T40/B
 impregnated against rust by resin
 the transformer are also available with other voltages
 corresponding to your wishes

Leistung power VA	Best.(BV)Nr./order No.							Maße/dimensions (mm)						Gewicht weight Kg.	
	PRI	100V	110V	115V	120V	127	Leistung VA	200V	A	B	C	D	E		F \varnothing
	SEC	230V						230V							
50	54300	54320	54340	54360	54380	125	54400	66	55	60	50	44	4,5	0,7	
100	54301	54321	54341	54361	54381	250	54401	66	67	60	50	56	4,5	1,0	
160	54302	54322	54342	54362	54382	400	54402	84	63	75	70	54	4,5	1,5	
250	54303	54323	54343	54363	54383	630	54403	96	80	87	80	68	6	2,2	
400	54304	54324	54344	54364	54384	1000	54404	96	90	87	80	78	6	2,7	
500	54305	54325	54345	54365	54385	1300	54405	96	104	87	80	92	6	3,4	