



Typ: ETV

Einphasen-Netztransformatoren  
 Einphasen-Sicherheitstransformator (SEC bis 50V)  
 Einphasen-Trenntransformator (SEC über 50V)  
 nach DIN/VDE 0551-EN60742-IEC742  
 Im Kunststoffgehäuse vergossen  
 dadurch sehr guter Feuchtigkeitsschutz  
 Schutzklasse II(schutzisoliert)  
 berührungssichere Schraubklemmen  
 kompakte Bauform, frei zugängliche Befestigungslöcher  
 Schutzart: Gehäuse IP65  
                   Klemmen IP20  
 PRI-Spannung: 230 V oder 400 V  
 SEC-Spannung: siehe Tabelle  
 Frequenz: 50/60 Hz  
 Isolationsklasse: T40/B  
 Andere Spannungen auf Anfrage lieferbar.

Type: ETV

Single-phase main transformers  
 single-phase isolating transformers (SEC up to 50V)  
 single-phase isolating transformers (SEC more than 50V)  
 according to DIN/VDE 0551-EN60742-IEC742  
 excellent protection against moisture by means of a  
 plastic enclosure and resin-encapsulated transformer  
 protection class II (totally insulated)  
 the terminals are protected against accidental  
 contact according to VBG 4  
 compact version, the fixing holes are easily accessible  
 type of protection: enclosure = IP65  
                                           terminal = IP20  
 PRI-voltage: 230 V or 400 V  
 SEC-voltage: see table  
 frequency: 50/60 Hz  
 isolations class: T40/B  
 the transformer are also available with other voltage and  
 different pin assignment corresponding to your wishes

Leistung power VA	Best.(BV)Nr./order No.											Maße/dimensions (mm)								Gew. Wt. Kg.	
	PRI	230 V										A	B	C	D	E	F	GØ	H		
		SEC	12V	15V	18V	20V	22V	24V	26V	28V	115V										230V
80	56840	56845	56850	56855	56860	56865	56870	56875	56880	56885	120	78	75	102,5	45	10	5,2	13	1,9		
100	56841	56846	56851	56856	56861	56866	56871	56876	56881	56886	120	78	75	102,5	45	10	5,2	13	1,9		
130	56842	56847	56852	56857	56862	56867	56872	56877	56882	56887	133	85	85	115	50	10	5,2	13	2,8		
160	56843	56848	56853	56858	56863	56868	56873	56878	56883	56888	133	85	85	115	50	10	5,2	13	2,8		
200	56844	56849	56854	56859	56864	56869	56874	56879	56884	56889	133	99	85	115	64	10	5,2	13	3,3		
	PRI	400 V																			
80	56890	56895	56900	56905	56910	56915	56920	56925	56930	56935	120	78	75	102,5	45	10	5,2	13	1,9		
100	56891	56896	56901	56906	56911	56916	56921	56926	56931	56936	120	78	75	102,5	45	10	5,2	13	1,9		
130	56892	56897	56902	56907	56912	56917	56922	56927	56932	56937	133	85	85	115	50	10	5,2	13	2,8		
160	56893	56898	56903	56908	56913	56918	56923	56928	56933	56938	133	85	85	115	50	10	5,2	13	2,8		
200	56894	56899	56904	56909	56914	56919	56924	56929	56934	56939	133	99	85	115	64	10	5,2	13	3,3		